WHITE CEMENT

1 /1 Mile shart

Blends with raw materials to suit your project White cement for decorative finishes Add oxide for a coloured finish Conforms to AS3972

WHITE CEMENT

44

A A A

- / Blends with raw materials to suit your project
- Compatible with render and mortar plasticisers

lus pavers, statues and pool interiors

- Add oxide for a deeper, coloured finish
- Conforms to AS3972

CEMENT AUSTRALIA

cementaustralia.com.au or call 1300 CEMENT (1300 236 368)



WHITE CEMENT

Blends with raw materials to suit your proj White cement for decorative finishes Add oxide for a coloured finish Conforms to AS3972





GROUT





Cement Australia's White Cement can be used with additives and supplementary cementitious materials*; it is versatile across a large number of applications.

- ✓ Portland White Cement easy to batch, mix, lay, rake or iron
- ✓ Suitable for additive addition including Hydrated Lime, Clay, Brickies Own
- ✓ Quality product tested by Cement Australia's NATA accredited laboratory and backed with our national technical support
- ✓ Flexible and easy ordering alongside your other Cement Australia products
- High Early strength attainment
- ✓ 20% less GP cement is required to batch M3 Mortar and 25% less GP Cement for M4 Mortar

SUGGESTED MIX RATIOS

APPLICATION	CEMENT	SAND	AGGREGATE
Concrete – General Purpose	1	2	3
M3 Mortar	1	5	-
M3 Mortar – Enhanced Workability	1 6 - +1 Hydrated Lime		
M4 Mortar	1	4	-
Render	1	3	-

*Please note: Colour results may vary - the colour of the finished product may vary due to natural differences in raw materials. Any supplementary cementitious materials added can affect the resulting mortar or concrete colour.

PRODUCT DISCLAIMER

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

Safety Data Sheet available at cementaustralia.com.au

DIRECTIONS FOR USE

1. Combine cement, clean aggregate and sand in correct proportion in a non-porous vessel. Large jobs require a concrete mixer. Add a Cement Australia oxide to colour your project. Note: For a whiter finish, select 'white' sand.

2. Add clean water gradually and mix thoroughly. Use enough water to make a workable mix. Excess water ruins good concrete.

3. Use the product immediately after mixing. Keep moist for 7 days for the best results.

HINTS and TIPS

Admixtures such as air entrainers, thickening agents or plasticisers can be used but should always be used in accordance with the manufacturers' recommendations.

Where specific colour or other properties are required, a trial with the available materials should be undertaken before completing the actual job.

Item Code 14026 Cement Australia White Cement 20kg



